# MD2REVEAL

`md2reveal` converts a markdown based slide into a html-presentation for **reveal.js**, which is a HTML Presentation Framework from Hakim El Hattab.

# SCREENSHOT

# HOWTO

- **IN**: the markdown file `Markdown in` and the menu/mathjax - checkbutton

- **OUT**: the HTML-file `HTML out` will be generated using the template file `md2reval.temp` in the subdirectory `template.`

- **_in2out_**: takeover the `Markdown in` file name for the `HTML out` file name. The extension will be `*.html`.

# MARKDOWN - EXTENSIONS FOR SLIDES

- `---` → three dashes to separate slides
- `.notes:` for Notes (in front the period and including the colon!)
- `|||` → three vertical bars as a vertical seperator (
  **Note:** The vertical seperator must be in **front of the slide**, where the vertical branching started. Use the normal seperator (→ three dashes), and the branching stops hopefully ...
- Underline with three equals `===` for the title of the presentation (→ `title-tag`)

# CONFIG.JSON

You can edit and change the markdown extensions configuration in the JSON-file `config.json`

# CHECKBUTTONS

- **MathJax**: Support for MathJax (→ LaTeX-like Math-Formula).

    - **Note**: The Download of `MathJax.js` increases the load time.

- **Menu**: Support for reveal.js-menu, which is a nice Add-On for reveal.js.

☰

# NOTES → 1

- Without reveal.js the slide is a little bit ugly!

- The path to reveal.js in the generated HTML-file HTML   out reflects my own installation. You should fix it to your own needs.

- The reveal.js-menu is from Greg Denehy. It must be installed separately.

# NOTES ⟶ 2

- The proper use of `md2reveal` is based on the Python-Markdown module, which has to be installed first. Python-Markdown is a Python implementation of John Gruber's Markdown.

- `md2reveal` is a **python 2.7.x**-script . . .

# LICENSE

## Copyright (C) 2017 Walter Spiegel

# ABOUT

→ sp, 2017-01-26, Vers. 009

Mail: walter [dot] spiegel [at] web [dot] de